

Description & Sizes

C75 is a standard Euronorm spring steel, part of En10132.

It is a commonly used spring steel in a wide range of engineering applications.

We can supply in sheet and coil, from 0.10mm to 5mm in hardened and tempered condition.

Hardness

We stock in a range of hardnesses, from 420/500VPN.

Composition

	C75
Carbon	0.70-0.80%
Silicon	0.10-0.40%
Manganese	0.50-0.80%
Phosphorous	0.040% max
Sulphur	0.040% max

Related Specifications

C75 is related to:

CK75
1074
CS70
CS80
75Cr1

Condition Supplied

BSS Supply C75 in the following conditions:
Cold rolled hardened and tempered.



Applications

C75 is widely used for a range of spring and engineering applications including:

- Clutch Plates
- Springs
- Knives & Blades
- Wood Saws
- Hand Tools
- Agricultural Tools
- Shims
- Doctor Blades
- Biomass Stirrers

**Fast UK and
International
shipping**

Contact

For quotations and enquiries, or to place an order, please contact our customer service team.

Our office is open from:

8.30am - 5.00pm Mon-Thurs
8.30am - 3:45pm Fridays.

Tel: +44 (0)114 244 0527
Email: bss@steelstrip.co.uk

www.springsteelstock.co.uk



BSS Spring Steel Stock is a division of
Fernite of Sheffield Ltd. 1 Orgreave Road, S13 9LQ

